## **Datasheet**

## **Pendant LED** Light Type C, **7W**



LV-INT-PLLC07



5 C€ CB ↑





| Category              | Interior                               |
|-----------------------|--|
| Туре                  | Pendant Downlight                      |
| Installation Method   | Surface Mount / Pendant                |
| Rated Power           | 7W                                     |
| Color Temperature     | 3000k/4000k/5000k/6000k/2700k-6500k    |
| Color Rendering Index | ≥80                                    |
| Flux                  | 80-100lm/w                             |
| LED Type              | СОВ                                    |
| LED Chip              | Bridgelux/Cree/Citizen/OSRAM/Epistar   |
| LED Driver            | High efficiency LED Driver             |
| Beam Angle            | 90°                                    |
| Control Mode          | On-Off/0-10V/DALI/DALI-2 Tunable White |
| Lifespan              | 50,000 Hours                           |
| Type of protection    | IP20                                   |
| Color                 | White/Black/Gold                       |

The technical data represent rated values for an ambient temperature of  $25^{\circ}$ C. The data values for the luminous flux are initially subject to a tolerance of +/- 10% those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 10% K. No liability is assumed for typographical or printing errors. The general terms and conditions of LVX apply.

